



Recommended Fasteners

Large members require timber connectors other than nails. Bolts, lag screws, split rings and shear plates, and custom-made hardware are commonly used in heavy timber structures where the joint's strength must be greater than that which could be achieved with nails. These types of connectors should be corrosion-resistant or suitably coated to prevent corrosion and staining. Generally, the design of mechanically fastened joints must take into consideration a variety of factors such as end and edge-spacing distances, moisture content, service conditions, and the effect of the number of connectors used. Because the cost of fabricating and installing connections may amount to a large percentage of the cost of a heavy timber structure, it is important to engineer the details of a structure before designing the timber members.

Screws can be used to fasten decks. Double hot-dipped galvanized screws can be used, however, stainless steel screws are recommended. For most applications, a 304 (18-8) grade provides adequate corrosion resistance. For decks exposed to salt air, use 316 grade. Screws must be long enough to penetrate 1" (25 mm) into support members. Penetration of 1-1/4" is required for structural components.

Blind fastening systems create an attractive, fastener-free deck surface. They employ metal clips and/or joist top brackets that fasten the sides or bottom of the deck board to the joists so that no fasteners are visible. Blind fastening systems are the ideal complement to the beauty of Western Red Cedar decking.

Store Safely on Site

If there's any gap in time between buying and building, it's imperative that your wood is stored properly. Otherwise, your beautiful boards may sustain UV or water damage before you even get a chance to get your DIY groove on. So to ensure adequate protection from the elements, it's best to lay the wood flat, but stack it into some sort of a peak or tent a cover overtop to shed possible rain. It's also very important to elevate the entire pile off the ground and cover it with some sort of waterproof tarp, but don't completely seal up your bundle – air circulation is a good thing.

