



Western Red Cedar V-Joint Siding

Item	Thickness	Exposure	Coverage	Lengths	Finish	Seasoning	Grade
1 x 6 T&G V-Joint	11/16"	5"	240 LF/SQ	8' - 20'	Smooth/Rough	Kiln Dried	Elite Knotty
1 x 8 T&G V-Joint	11/16"	6-3/4"	180 LF/SQ	8' - 20'	Smooth/Rough	Kiln Dried	Elite Knotty

Application: Exterior and Interior
Siding & Paneling

Species: Western Red Cedar

Grade: Elite Knotty

Finish: Fully reversible (smooth/rough)

Features & Benefits:

- Milled from the finest quality fiber in North America
- Excellent for siding, soffit, patio ceilings, and accent walls
- No hole knotty Cedar
- Contains natural oils and resins that make it resistant to insects, rot, and decay

WP-4/WP-4

Technical drawing of a shaft with dimensions and a break symbol. The shaft has a total length of 5 7/16" - 7 1/8" - 9 1/8" - 11 1/8". The left end features a 1/4" R fillet and a 1/4" diameter hole. The right end features a 1/4" diameter hole and a 1/32" diameter hole. The shaft is shown with a break symbol in the middle.



1x6 V-Joint Smooth

9264 MANCHESTER RD. ST. LOUIS, MO 63144

PHONE: 314.706.5804 | EMAIL: SUPPORT@FP-CEDARSUPPLY.COM